


A母頭需與外模平齊



內埋螺母



L

DESCRIPTION CONTROL			
REV	DESC	DATE	ECN NO.
C	Δ	09.11.23	N20911271
D	Δ	09.11.27	N20911335
E	Δ	2010.08.05	自然切邊

CUSTOMER P/N	Y-S P/N	L&T	M	TE
RR-AA04TP-20G	UB0101300002866	508±20	0.51	100*1
RR-AA04TP-5G	UB0101300102866	127±10	0.13	



2PCS六角螺絲絲小  
PE袋內成品袋中  
▲

NOTE:  
REF: UB0101300002866  
ROHS COMPLIANT

RR-AA04TP-XXG  
客戶料號  
LABEL貼標材  
▲▲

*	300	PE-BAG2.5*2.5*100MM(袋,PCSS網絲)	▲	1	PCS
*	300	TUL-ABK		444	MM
*	300	LABEL-RR-AA04TP-XXG *4*15MM	▲▲	1	PCS
*	33001001035	LABEL-40*25MM TUSB* (PVC材質)		1	PCS
*	300	CARTON-66*30*25CM		1/50	PCS
*	300	PE-BAG-30*25*100MM		1/50	PCS
*	300	PE-BAG-5*6*100MM		1	PCS
*	300	PVC-BK10050		8.0	G
7	240010700138	SRW-5.4*9.8 <全牙 4-10UNC>		2	PCS
6	240020000008	NUTS-4.75*2.0MM<40UNC>		2	PCS
5	300	PC-5321		5.0	G
4	300	PC-CBK10020		13.5	G
3	110083304038	USB-A-5<WH> <鍍鉻鍍金>		1	PCS
2	110083304129	USB-A-4*12<WH><SHORNT> <鍍鉻鍍金>		1	SET
1	1303041100003	UL2725-1P+2CM+AB.BK.1R.10.0D-4.8 (2820-REV.210)		L	M

PIN ASSIGNMENT

P1	P2
1	1
2	2
3	3
4	4
5	5

1	RED	1
2	WHITE	2
3	GREEN	3
4	BLACK	4
5	BR.AID	5

www.USBFireWire.com



ITEM: RR-AA04TP-XXG  
SCALE: NONE  
DATE: 2009.09.08  
CUSTOMER C331 瑞鴻  
PAGE: 1/1  
CUSTOMER P/N: RR-AA04TP-XXG ▲

ALL DIMENSIONS IN mm