



4564

P1		P2
2	_____	1
3	_____	3
1	_____	2
5	_____	4
6	_____	6
4	_____	5
8	_____	7
9	_____	9
7	_____	8
11	_____	10
12	_____	12
10	_____	11
14	_____	13
13	_____	17
18	_____	18
15	_____	15
16	_____	16
17	_____	14
19	_____	19
SHIELD	_____	SHIELD

NOTE: All relevant materials are complied with RoHS directive .

No.	DESCRIPTION	Q'TY	Supplier
3	UL1061 28AWG INSULATOR WIRE, LENGTH 25mm, ID0.9, DRAWING No.EH002801C-024	1	M304
	MOLDED PE COLOR TRANSPARENT		M280
	MOLDED PVC BLACK		M304
	COPPER FOIL 25*40mm	1	M309
	PCB: MSL-73	1	M730
2	HDMI 19 FEMALE, GOLD PLATING 15u' ON CONTACTS & GOLD CONNECTOR, BLACK INSULATOR,PCB TYPE	1	M83
1	HDMI C 19 MALE, GOLD PLATING 15u' ON CONTACTS & GOLD CONNECTOR, BLACK INSULATOR(R-S160S-3),PCB TYPE	1	M24
APPROVED		www.USBFireWire.com	
CHECKED	HU		
DRAWING	JIANG		
DATE	10/AUG/11	ITEM NO.	RR-HDMI-AFCM
		UNIT:mm	

Cable Length Unless Other Spec.
Tolerances:
0 ~200mm ±10mm
201~1000mm ±20mm
1001 ~1500mm ±25mm
1501~2100mm ±30mm
2100mm↑ ±40mm

CHECKED