


ROHS Compliant

ELECTRICAL CHARACTER:

- 100% OPEN & SHORT TESTING;
- WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- INSULATION RESISTANCE:5M Ohm (Min);
- CONDUCTIVE RESISTANCE:3 Ohm (Max)

65P Black PVC											
HDMI CM,BLACK INSULATION,SHELL 3U"											
GOLD PLATED WITH SOLDER(P/N YQT-HCM3)											
HDMI DM,BLACK INSULATION,SHELL 3U"											
GOLD PLATED WITH SOLDER(P/N YQT-HDM3)											
(1P*30AWG+AL)*5C+5C*30AWG+AL+D+B OD4.5											
L=12in/24in/6ft Black											
Descriptron		Q' TY		Unit		ANGLE		DATE		SCALE	
										1:1	
										UNIT	
										mm	



USB FIREWIRE.com

THE INFORMATION CONTAINED HEREIN IS THE PROPRIETARY INFORMATION OF RR BUSINESS VENTURES, LLC. THE POSSESSOR AGREES TO MAINTAIN THIS DOCUMENT IN CONFIDENCE; NOT REPRODUCE IT OR COPY IT, AND NOT TO REVEAL OR PUBLISH IT IN WHOLE OR PART.

COPYRIGHT © 2019

Tolerance, Unless Otherwise Specified

UP TO 5	±0.2
ABOVE 5 --30	±0.3
ABOVE 30--50	±0.4
ABOVE 50	±0.5
ANGLE	±3°

DRAW:

CHECKED:

APPROVED:

DATE

TITLE

PART NO.

DRAW NO.

SCALE

HDMI CM TO DM

RR-7D-5S-XXGX