



9142-1

P1		P2	
1	—	1	RED
2	—	2	WHITE
3	—	3	GREEN
4	—	4	BLACK
5	—	8	BLUE
6	—	9	YELLOW
7	—	7	SHIELD
8	—	5	PURPLE
9	—	6	ORANGE
7	—	7	SHIELD
SHIELD	—	SHIELD	SHIELD

NOTE: All relevant materials are complied with RoHS directive .

3	BLACK HEAT SHRINK TUBE $\phi 1.0 \times 3\text{mm}$	2	M743
	BLACK HEAT SHRINK TUBE $\phi 3.0 \times 9\text{mm}$	4	M743
	MOLDED PVC BLACK		M304
2	USB 3.0 CABLE, 28AWG*1PAIR+(28AWG*1PAIR+D+F-AL)*2PCS+24AWG*2C+AMA BRAID, OD 5.8mm JACKET BLACK, DRAWING NO. EUAB2801P2802P2402C-333	L-20mm	M304
1	USB A MALE 3.0, GOLD PLATING 30u" ON CONTACTS BLUE INSULATOR, SHORT TYPE(CHUSB3AM01D)	2set	M108
No.	DESCRIPTION	Q'TY	Supplier
APPROVED		Cable Length Unless Other Spec. Tolerances: 0 ~200mm $\pm 10\text{mm}$ 201~1000mm $\pm 20\text{mm}$ 1001 ~1500mm $\pm 25\text{mm}$ 1501~2100mm $\pm 30\text{mm}$ 2100mm $\uparrow$ $\pm 40\text{mm}$	
CHECKED	HU		
DRAWING	MEI		
DATE	26/MAY/11	ITEM NO.	RR-AMX2-XXR

www.USBFireWire.com

