

Connector 1





Standard C to C
RR-USB2W-C-C

Connector 2



Pin Assignment

P1	C to C - w/eMarker				P2
1 - A4,B4,A9,B9		Red		1 - A4,B4,A9,B9	
2 - A7		White		2 - A7	
3 - A6		Green		3 - A6	
4 - A5		Blue		4 - A5	
5 - B5		Yellow		5 - B5	
6 - A1,B1,A12,B12,Shell		Black		6 - A1,B1,A12,B12,Shell	
Shell		Shield		Shell	

Materials	RR-CSX2-XXGN	
Wire		RR-USB2W-C-C Standard C to C - 6 Wire, 24AWG x 2 28AWG x 4 - 5.0mm OD
	Standard C to C	
	Connector 1 2CS C - Straight	Connector 2 2CS C - Straight
Connector Part Number	RR-83005-M0008_noIC	RR-83005-M0009_IC
Outer Mold Number	RR-CS-OVER MOLD	RR-CS-OVER MOLD
Material Options	PVC-45 - Polyvinyl chloride	PVC-45 - Polyvinyl chloride
Inner Mold Number	RR-CS-INNER MOLD	RR-CS-INNER MOLD
Inner Mold Material	LPKY - Low Pressure Material	LPKY - Low Pressure Material
Heat Shrink	N/A	N/A

Part Number		Unit	Length	+	-
RR-CSX2-06GN		Inches	6	0.5	0
RR-CSX2-30GN		Inches	30	1	0
RR-CSX2-50GN		Inches	50	1.5	0
RR-CSX2-180GN		Inches	180	3	0
Date	August 23, 2024				
Design By	Rick Wessley				
Revision	1				
Comments	N/A				